



Stanley DCP30 12 VDC Water Pump

- Voltage Requirement 12 vdc
- Current 9.5 amps
- Maximum Water Flow 12.5 lpm
- Maximum Water Pressure 2.8 bar
- Cut-Out Pressure 3.1 bar
- Cut-In Pressure 2.1 bar



Stanley SM20 Water Pump

- Capacity 2-1/2 in. Discharge
- Performance 250 gpm (946 lpm)
- Flow range 15 - 34 lpm
- Pressure 70 - 140 bar
- Weight 6.3 kg



Stanley SM21 Water Pump

- Capacity 2-1/2 in. Discharge
- Performance 1135 lpm
- Flow range 15 - 34 lpm
- Pressure 70 - 140 bar
- Weight 20 lbs (9.1 kg)



Stanley SM50 Water Pump

- Outlet size 3 - inch NPT / 3 - inch Camlock
- Output capacity 1890 lpm
- Weight 9.5 kg
- Input pressure 69 - 138 bar
- Input flow range 26 - 45 lpm



Stanley TP03 Trash Pump

- Capacity 3 in. Discharge
- Performance 1688 lpm
- Flow range 26 - 34 lpm
- Pressure 140 bar
- Weight 14 kg



Stanley TP08 Trash Pump

- Capacity 3,028 lpm
- Weight 26.7 kg
- Pressure 140 bar
- Flow Range 26-34 lpm
- Maximum Flow 34 lpm
- Inlet Diameter 100 mm



WP 25 SUBMERSIBLE WATER PUMP

- Flow: 1600 L/min (96 Cubic mxh)
- Water head max: 45 meter
- Pumpable solids dimension: 2 cm
- Impeller type: Centrifugal open impeller
- Oil flow: 15 - 38 l/min
- Oil pressure: 100 - 210 bar



SP 20 TRASH WATER PUMP

- Outlet mouth: 2" BSP female
- Flow: 800 L/min (48 Cubic mxh)
- Water head max: 35 meter
- Pumpable solids dimension: 3 cm
- Oil flow: 15 - 30 l/min
- Oil pressure: 100 - 210 bar



SP 35 SUBMERSIBLE TRASH PUMP

- Outlet mouth: 3" BSP female
- Flow: 1900 L/min (114 Cubic mxh)
- Water head max: 35 meter
- Pumpable solids dimension: 5 cm
- Oil flow: 15-38 l/min
- Oil pressure: 100 - 210 bar



SP 45 TRASH WATER PUMP

- Outlet mouth: 4" BSP female
- Flow: 3000 L/min (180 Cubic mxh)
- Water head max: 16 meter
- Pumpable solids dimension: 7 cm
- Oil flow: 30-45 l/min
- Oil pressure: 140 - 210 bar



SP 55 SUBMERSIBLE TRASH PUMP

- Outlet mouth: 5" BSP female
- Flow: 5500 L/min (330 Cubic mxh)
- Water head max: 29 meter
- Pumpable solids dimension: 5,5 cm
- Oil flow: 60 - 100 l/min
- Oil pressure: 150 - 350 bar



SP 65 SUBMERSIBLE PUMP

- Outlet mouth: 6" BSP female
- Flow: 8000 L/min (480 Cubic mxh)
- Water head max: 39 meter
- Pumpable solids dimension: 6,5 cm
- Oil flow: 60 - 100 l/min
- Oil pressure: 150 - 350 bar



SG4 SLURRY GATE (OPTION SP 45, 55, 65)

- SG4 body and cylinder, this element to be installed on the pump outlet mouth.
- Fluid passage: equals to 6"
- Total height: 370 mm
- Cylinder type: double effect
- Control valve: 3 position open centre